

# DECLARATION OF PERFORMANCE CE58



1. Product Type: **Large End Closure Block 505mm**
2. Identification: **Product ID code is shown on delivery ticket**
3. Intended Use: **In walls, columns and partitions**
4. Manufacturer: **Thomas Armstrong (Holdings) Ltd Workington Rd, Flimby, Maryport, Cumbria. CA15 8RY**
5. Authorised Representative: **Not applicable**
6. AVCP: **System 4**
7. Harmonised Standard: **EN 771-3 : 2011**
8. ETA: **Not Relevant**
9. Declared Performance:

Essential Characteristics		Performance	Harmonised technical specification
Dimensions	Length, mm	505	EN 771-3 : 2011
	Width, mm	140	
	Height, mm	100	
Dimensional Tolerance		D1 (Flatness NPD, Plane Parallelism NPD)	
Configuration	Shape & features	NPD	
	Group according to EN 1996-1-1 (EC6)	Group 1	
Compressive strength	Mean compressive strength, N/mm <sup>2</sup>	7.3 (┴ bed face, whole unit) (Cat II)	
	Direction of load	Perpendicular to bed faces	
	Unit category	Category II	
Dimensional stability	Moisture Movement, mm/m	0.6	
Bond strength	Shear bond strength, N/mm <sup>2</sup>	0.15 with GPLM	
	Flexural bond strength	NPD	
Reaction to fire		A1 (Commission Decision 2000/605/EC)	
Water absorption, gm <sup>2</sup> .s <sup>-0.5</sup>		NPD	
Water vapour permeability		5/15 (tabulated value)	
Direct airbourne sound insulation	Gross density, kg/m <sup>3</sup>	2000	
	Configuration; dimensions & tolerances	See configuration	
Thermal Conductivity, W/mK (A <sub>10, dry</sub> ) ρ = 50%		1.05 Dry value - design values require correction for moisture content. See product literature.	
Durability against freeze / thaw		For use below and above ground level	
Dangerous substances		See Note	

Note: Information on Dangerous Substances will only be given when and where required in the appropriate form.  
See Annex ZA of BS EN 771-4:2069

10. The performance of the product identified in 1 and 2 is in conformity with the declared performance in 9.

This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in 4.

Signed on behalf of the manufacturer:

J Mason (Technical Manager)  
Brompton-on-Swale, North Yorkshire. 1st June 2013



Thomas Armstrong (Holdings) Ltd Workington Rd, Flimby, Maryport, Cumbria. CA15 8RY

13

CE58

EN 771-3 : 2011

## Large End Closure Block 505mm

Category II aggregate concrete masonry unit

Dimensions	Length, mm	505
	Width, mm	140
	Height, mm	100
Dimensional Tolerance	Category	D1 (Flatness NPD, Plane Parallelism NPD)
Configuration	Shape & features	NPD
	Group according to EN 1996-1-1 (EC6)	Group 1
Compressive strength	Mean compressive strength, N/mm <sup>2</sup>	7.3 (┴ bed face, whole unit) (Cat II)
	Direction of load	Perpendicular to bed faces
	Unit category	Category II
Dimensional stability	Moisture Movement, mm/m	0.6
Bond strength	Shear bond strength, N/mm <sup>2</sup>	0.15 with GPLM
	Flexural bond strength	NPD
Reaction to fire		A1 (Commission Decision 2000/605/EC)
Water absorption, gm <sup>2</sup> .s <sup>-0.5</sup>		NPD
Water vapour permeability		5/15 (tabulated value)
Direct airbourne sound insulation	Gross density, kg/m <sup>3</sup>	2000
	Configuration; dimensions & tolerances	See configuration
Thermal Conductivity, W/mK (A <sub>10, dry</sub> ) ρ = 50%		1.05 Dry value - design values require correction for moisture content. See product literature.
Durability against freeze / thaw		For use below and above ground level
Dangerous substances		See Note

Note: Information on Dangerous Substances will only be given when and where required in the appropriate form.  
See Annex ZA of BS EN 771-4:2069

See also Declaration of Performance CE58