

DECLARATION OF PERFORMANCE UKCA 07



- Product Type: **Airtec Seven Foundation 140 block**
- Identification: **Product ID code is shown on delivery ticket**
- Intended Use: **In walls, columns and partitions**
- Manufacturer: **Thomas Armstrong (Holdings) Ltd Workington Rd, Flimby, Maryport, Cumbria. CA15 8RY**
- Authorised Representative: **Not applicable**
- AVCP: **System 2+**
- Designated Standard: **BS EN 771-4 : 2011**
- ETA: **British Board of Agrément, PO Box 195, Bucknalls Lane, Garston, Watford. WD25 7NG (NB 0836)**

9. Declared Performance:

Essential Characteristics		Performance	Designated technical specification
Dimensions	Length, mm	620	BS EN 771-4 : 2011
	Width, mm	Various - shown on the delivery documentation	
	Height, mm	140	
Dimensional Tolerance		TLMB (Flatness 1.0mm, Plane Parallelism 1.0mm)	
Configuration	Shape & features	NPD	
	Group according to EN 1996-1-1 (EC6)	Group 1	
Compressive strength	Mean compressive strength, N/mm ²	7.3 (┴ bed face, whole unit) (Cat I)	
	Direction of load	Perpendicular to bed faces	
	Unit category	Category I	
Dimensional stability	Moisture Movement, mm/m	0.4	
Bond strength	Shear bond strength, N/mm ²	0.15 with GPLM 0.30 with TLM	
	Flexural bond strength	NPD	
Reaction to fire		A1 (Commission Decision 2000/605/EC)	
Water absorption, gm ² .s ^{-0.5}		NPD	
Water vapour permeability		5/10 (tabulated value)	
Direct airborne sound insulation	Gross density, kg/m ³	730	
	Configuration; dimensions & tolerances	See configuration	
Thermal Conductivity, W/mK (λ _{10, dry}) ρ = 50%		0.15 Dry value - design values require correction for moisture content. See product literature.	
Durability against freeze / thaw		For use below and above ground level	
Dangerous substances		See Note	

Note: Information on Dangerous Substances will only be given when and where required in the appropriate form.
See Annex ZA of BS EN 771-4:2011

10. The performance of the product identified in 1 and 2 is in conformity with the declared performance in 9.

This Declaration of Performance is issued under the sole responsibility of the manufacturer identified in 4.

Signed on behalf of the manufacturer:

J Mason (Technical Manager)

J Mason

Brompton-on-Swale, North Yorkshire.

1st August 2021



0836

Thomas Armstrong (Holdings) Ltd Workington Rd, Flimby, Maryport, Cumbria. CA15 8RY

21

UKCA 07

BS EN 771-4 : 2011

Airtec Seven Foundation 140 block

Category II autoclaved aerated concrete masonry unit

Dimensions	Length, mm	620
	Width, mm	Various - shown on the delivery documentation
	Height, mm	140
Dimensional Tolerance	Category	TLMB (Flatness 1.0mm, Plane Parallelism 1.0mm)
Configuration	Shape & features	NPD
	Group according to EN 1996-1-1 (EC6)	Group 1
Compressive strength	Mean compressive strength, N/mm ²	7.3 (┴ bed face, whole unit) (Cat I)
	Direction of load	Perpendicular to bed faces
	Unit category	Category I
Dimensional stability	Moisture Movement, mm/m	0.4
Bond strength	Shear bond strength, N/mm ²	0.15 with GPLM 0.30 with TLM
	Flexural bond strength	NPD
Reaction to fire		A1 (Commission Decision 2000/605/EC)
Water absorption, gm ² .s ^{-0.5}		NPD
Water vapour permeability		5/10 (tabulated value)
Direct airborne sound insulation	Gross density, kg/m ³	730
	Configuration; dimensions & tolerances	See configuration
Thermal Conductivity, W/mK (λ _{10, dry}) ρ = 50%		0.15 Dry value - design values require correction for moisture content. See product literature.
Durability against freeze / thaw		For use below and above ground level
Dangerous substances		See Note

Note: Information on Dangerous Substances will only be given when and where required in the appropriate form.
See Annex ZA of BS EN 771-4:2011

See Declaration of Performance: UKCA 07